



Laserlite® Accessories

...for a professional finish


- Fixings
- Infill strips
- Noise stop tape
- Back channel & infill strips



Fixings Laserlite® One Shot® Time Saving Fixing System saves 50% installation time as no pre-drilling is required. As a guide you will need approximately 7 fixings per lineal metre.

Timber One Shot® Fixing

Expansion hole cutter Laserlite® weather seal



Specifications


- Coated to AS3566 Class 4
- 12 gauge
- 11 threads per inch
- Suitable for use with treated timber
- Type 17 (shape of tip)
- Suitable for use with 5/16" drive
- Cuts 11mm expansion hole
- Suitable for drill speed use -1000rpm

Length available 50mm 65mm

	✓	
corrugated		
	✓	
greca		
		✓
5 - rib		

Steel One Shot® Fixing

Expansion hole cutter Laserlite® weather seal



Specifications

- Coated to AS3566 Class 4
- 12 gauge
- 14 threads per inch
- Suitable for battens .75-4.5mm thick
- Suitable for use with 5/16" drive
- Hex head
- Cuts 11mm expansion hole
- Suitable for drill speed use - 2000rpm

Length available 60mm

	✓
corrugated	
	✓
greca	
	✓
5 - rib	

Select the quantity that suits your needs

- One Shot 50mm Timber**
- One Shot 65mm Timber**
- One Shot 60mm Metal**
- One Shot Standard Timber**
- One Shot Standard Metal**





Profile

- Corrugated, Greca
- 5 Rib
- Corrugated, Greca, 5 Rib
- Corrugated, Greca, 5 Rib
- Corrugated, Greca, 5 Rib

Pack Size

- 50 packet | 250 tub | 1000 box
- 50 packet | 200 tub | 500 box
- 50 packet | 200 tub | 500 box
- 50 packet
- 50 packet

One step easy installation



1. Firmly place the sharp point of the One Shot fixing onto the crest of the corrugation to eliminate 'skidding or wandering'.

2. Commence drilling at 1000rpm (timber) 2000rpm (steel) to pierce the sheet. Screw engages in timber or steel batten.

3. Cutter engages polycarbonate sheet, cuts the expansion hole and centers the fixing.

4. Wait until the rubber weather seal engages and compresses against the roof sheet and under the fixing head to stop.



Eave Infill Strips

Prevent rain, dust and wind entering eaves

	LENGTH	COLOUR
Corrugated infill strips	920mm	white or black
Greca infill strips	940mm	white or black
5-Rib infill strips (top & bottom)	750mm	white or black



All infill strips come in packs of 4



Noise Stop Tape

Reduces creaking



	LENGTH	COLOUR
Noise Stop Tape	20m	white



Back Channel and Infill

Prevents leaking at walls and facias

	LENGTH	COLOUR
Back channel (Corrugated and Greca)	3.6m	grey
Back channel (5-Rib)	3.6m	grey
Back channel Infill Strip (Corrugated and Greca)	3.6m	white
Back channel Infill Strip (5-Rib)	3.6m	white



All back channel infills come in packs of 1

For further technical assistance please refer to your local Laserlite® distributor, contact details - www.laserlite.com.au.

